

## Product Description:

**EMULTEX 301** is an acrylic-based ready-mixed texturing compound for use on all types of interior and exterior ceilings and walls. **EMULTEX 301** is a versatile product that can be applied with a selection of application tools and rollers to give a wide range of attractive textures and finishes. **EMULTEX 301** gives surfaces an attractive white finish that covers hairline cracks and minor blemishes. It is easy to apply and allows the user to create innovative patterns and effects.

## Properties:

**EMULTEX 301** is made from a selected blend of acrylic and precisely graded fillers.

## Area of Use:

**EMULTEX 301** is ideal for cementitious materials, gypsum board, wood, and all common building surfaces.

## Advantages:

- ) Easy to use.
- ) High adhesion power.
- ) High filling capacity.
- ) Different finishing depending on tools used.
- ) Environmentally friendly.

## Technical Information:

<b>Product Type</b>	Decorative Coating
<b>Binder</b>	Acrylic
<b>Colours</b>	White - can be tinted
<b>Initial Drying Time</b>	1 - 2 hours
<b>Recoat In</b>	6 hours
<b>Final Drying Time</b>	16 - 18 hours
<b>Solid Content By Weight</b>	79% (± 2%)
<b>Specific Gravity</b>	1.8 (± 0.05)
<b>Dilution</b>	With water if needed
<b>Average consumption Rate</b>	0.7 - 1 m <sup>2</sup> /Kg/Coat depending on surface condition (smooth Texture) 0.3 - 0.7 m <sup>2</sup> /Kg/Coat depending on surface condition (medium Texture) 0.25 - 0.3 m <sup>2</sup> /Kg/Coat depending on surface condition (rough Texture)
<b>Shelf Life &amp; Storage</b>	2 years from the production date provided - store in sealed original packages away from direct sunlight

## Method of Use:

### Surface Preparation:

- Make sure the surface is clean, clear, sound and free of grease and foreign matter.
- Prime the surface using **SUPER SEAL 123** primer from **ORIENT**.

### Finishing:

- Apply **EMULTEX 301** using the right tools to achieve the desired finishing.
- Clean tools using normal tap water.

## Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

## Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website [www.orient-paints.com](http://www.orient-paints.com) or call 19842.