

Product Description:

KRETAL GLOSS 444 is a superior quality high-gloss enamel paint based on high-quality alkyd resins, selected pigments and other additives. It is designed to give the advantage of opacity, durability and hiding power.

Properties:

KRETAL GLOSS 444 is based on high-quality alkyd resins, pigments, and other additives.

Area of Use:

KRETAL GLOSS 444 is ideal for use on wood, soft and hard board, concrete, plaster, and new iron (after priming).

Advantages:

- High-gloss.
- High coverage rate.
- Weather resistant.
- High durability.

Technical Information:

Product Type	Gloss Enamel Finish
Binder	Alkyd
Colours	White - can be tinted using Orient tinting System
Initial Drying Time	2 - 3 hours
Recoat In	18 - 24 hours
Final Drying Time	24 Hours
Viscosity@ 25c	130 - 135 ku
Solid Content By Volume	From 45 to 49 (according to the colour) (± 2%)
Solid Content By Weight	From 59 to 64 (according to the colour) (± 2%)
Specific Gravity	From 0.99 to 1.17(according to the colour) (± 0.03)
Dilution	White spirit
Average Consumption Rate	12 - 15 m ² /Ltr/Coat (depending on surface condition)
Shelf Life & Storage	3 years from the production date provided - store in sealed original packages away from direct sunlight

Method of Use:

Surface Preparation:

- Make sure the surface is clean, clear, sound and free of grease and dust.
- Apply one coat of **PRIMOL 401** by brush, roller or spray onto metal surfaces.
- Apply one coat of **SUPER SEAL 123** by brush, roller or spray on non-steel surfaces.
- For non-metal surfaces level and smooth down the surface using 2 coats of **ACRYLIC 1000 PUTTY**.
- Apply one coat of **KRETAL MATT 422** from **ORIENT** as an undercoat.

Finishing:

- Apply two coats of **KRETAL GLOSS 444** from **ORIENT** as a finishing coat.
- Clean tools using normal white spirit.

Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website www.orient-paints.com or call 19842.