

## Product Description:

**KRETAL MATT 422** is a high-quality matt enamel paint based on high-quality alkyd resins, selected pigments and additives. It is designed to give the advantage of opacity, adhesion, durability and hiding power.

## Properties:

**KRETAL MATT 422** is based on high quality alkyd resins, pigments, and additives.

## Area of Use:

**KRETAL MATT 422** is ideal for use on wood, soft and hard board, concrete, plaster and new iron (after priming). It can be used as an undercoat for **GLOSS** paints, or modified to be used as a filler (**PUTTY**).

## Advantages:

- High coverage rate.
- Weather resistant.
- High durability.
- Easy to use.
- High yellowing resistance.

## Technical Information:

<b>Product Type</b>	Matt Enamel Finish
<b>Binder</b>	Alkyd
<b>Colours</b>	White - can be tinted using Orient tinting System
<b>Initial Drying Time</b>	30 minutes
<b>Recoat In</b>	3 - 4 Hours
<b>Final Drying Time</b>	24 Hours
<b>Viscosity@25c</b>	80 - 85 ku
<b>Solid Content By Volume</b>	From 53 to 60 (according to colour) (± 2%)
<b>Solid Content By Weight</b>	From 74 to 79 (according to colour) % (± 2%)
<b>Specific Gravity</b>	From 1.43 to 1.53( according to colour) (± 0.03)
<b>Dilution</b>	White Spirit
<b>Average Consumption Rate</b>	12 - 14 m <sup>2</sup> /Ltr/Coat (depending on surface condition)
<b>Shelf Life &amp; Storage</b>	2 years from the production date provided - store in sealed original packages away from direct sunlight

## Method of Use:

### Surface Preparation:

- Make sure the surface is clean, clear, sound and free of grease and dust.
- Apply one coat of **PRIMOL 401** from **ORIENT** using a brush, roller or spray on metal surfaces.
- Apply one coat of **SUPER SEAL 123** from **ORIENT** using a brush, roller or spray onto non-steel surfaces.
- Apply two coats of **ACRYLIC 1000 PUTTY** from **ORIENT** onto non-steel surfaces.

### Finishing:

- Apply two coats of **KRETAL MATT 422** from **ORIENT**.
- Clean tools using white spirit.

## Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

## Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website [www.orient-paints.com](http://www.orient-paints.com) or call 19842.