

Product Description:

SPEEDO 510 is a highly durable gloss wood lacquer for interior use. It is designed for use on wooden surfaces subject to heavy wear such as floors, stairs, and worktops.

Properties:

SPEEDO 510 is one-component varnish manufactured from alkyd resins.

Area of Use:

SPEEDO 510 is ideal for use on wood flooring, worktops, stair cases, and other wooden areas subject to heavy wear.

Advantages:

- Transparent.
- High gloss.
- Does not affect wood colour.
- High adhesion.
- Resistant to household chemicals and hot water.

Technical Information:

Product Type	Wood Varnish
Binder	Alkyd
Colours	Transparent - can be tinted using Orient Wood Colour Chart
initial drying time	3 hours
viscosity @ 25 c	135-140 ku.
Solid content By volume	60.2% (± 2%)
Solid content By Weight	67.3% (± 2%)
Specific gravity	0.93 (± 0.02)
dilution	White Spirit
Average consumption Rate	12 - 15 m ² /Ltr/Coat (depending on surface condition)
Shelf Life & Storage	3 Years from the production date provided storage in sealed original packages away from direct sunlight

Method of Use:

- Make sure the surface is clean, clear, sound and free of grease and dust.
- Apply two or three coats of **NITRO SEAL 566** by brush, roller or spray.
- Apply two coats of **SPEEDO 510** from **ORIENT**.
- Clean tools using white spirit.

Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website www.orient-paints.com or call 19842.