

Product Description:

STYLE PRIMOL is a high-solids rust-inhibitive alkyd primer with anti-corrosive properties. It is easy to apply by spray, is fast drying, and can be top-coated with alkyd and latex coatings.

Properties:

STYLE PRIMOL is a high-solids rust-inhibitive compound.

Area of Use:

STYLE PRIMOL is ideal for architectural and light commercial construction, and is ideal for application on steel to protect against atmospheric exposure. With excellent impact resistance, it is also suitable for use on vehicles.

Advantages:

- Easy to use.
- Fast drying.
- Easy to smooth down (sand).
- Impact resistant.

Technical Information:

Product Type	Anti-Corrosion Primer
Binder	Alkyd Resin
Colours	Grey - Red
Initial Drying Time	30 mins
Recoat In	3 - 4 Hours
Final Drying Time	24 Hours
Viscosity @ 25c	125 - 130 ku
Solid Content By Volume	62% (± 2%)
Solid Content By Weight	83% (± 2%)
Specific Gravity	1.66 (± 0.02)
Dilution	White Spirit
Average Consumption Rate	12 - 16 m ² /Ltr/Coat (depending on surface condition)
Shelf Life & Storage	1 year from the production date provided - store in sealed original packages away from direct sunlight

Method of Use:

-) Make sure the surface is clean, clear, sound and free of grease and foreign matter.
-) Apply one coat of **STYLE PRIMOL** by brush, roller or spray.
-) Sand lightly and apply another coat of **STYLE PRIMOL** if needed.
-) Apply the top coat (**KRETAL MATT 422** or **KRETAL GLOSS 444**).
-) Clean tools using white spirit.

Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available on request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website www.orient-paints.com or call 19842.