

## Product Description:

**STYLE WATER SEALER 121** is a product absorbed deeply into the substrate of cementitious materials, plasters and limes. It binds the substrate and the surface to give a solid base for painting.

## Properties:

**STYLE WATER SEALER 121** is made from aqueous acrylic.

## Area of Use:

**STYLE WATER SEALER 121** for interior use on sand/cement render, cast-in-situ, blockwork, precast concrete and lightweight concrete. Is especially suitable for sealing old, dry, absorbent, untreated concrete.

## Advantages:

- Easy to use.
- Improves adhesion.
- Binds dusting substrates.
- Reduces efflorescence and surface alkalinity.
- Reduces the consumption rates of finishing materials.
- Environmentally friendly.

## Technical Information:

<b>Product Type</b>	Primer/Sealer
<b>Binder</b>	Acrylic
<b>Colours</b>	White
<b>Initial Drying Time</b>	20 - 30 mins
<b>Recoat In</b>	2 - 4 Hours
<b>Final Drying Time</b>	24 Hours
<b>Viscosity @ 25c</b>	115 – 120 ku
<b>Solid Content By Volume</b>	33% (± 2%)
<b>Solid Content By Weight</b>	53% (± 2%)
<b>Specific Gravity</b>	1.43 (± 0.02)
<b>Dilution</b>	With water if needed
<b>Average Consumption Rate</b>	8 - 11 m <sup>2</sup> /Ltr/Coat (depending on surface condition)
<b>Shelf Life &amp; Storage</b>	2 years from the production date provided - store in sealed original packages away from direct sunlight

## Method of Use:

- Make sure the surface is clean, clear, sound and free of grease and foreign matter.
- Apply one coat of **STYLE WATER SEALER 121** by brush, roller or spray.
- Clean tools using normal tap water.

## Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

## Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website [www.orient-paints.com](http://www.orient-paints.com) or call 19842.