

Product Description:

SUPER GLAZE 711 is a high-quality product designed to give different effects such as marbling or aging.

Area of Use:

SUPER GLAZE 711 is suitable for most old and new building surfaces such as plastered walls, gypsum board, fair-faced concrete and plywood. It is ideal for use in apartments, villas, recreational areas, office buildings and hotels.

Advantages:

- Excellent decorative effect.
- Low consumption rate.
- Excellent weather resistance.
- Washable.

Technical Information:

Product Type	Aging Clear Topcoat
Binder	Alkyd
Colours	Clear - can be tinted
Initial Drying Time	2 - 4 hours
Recoat In	9 - 12 hours
Final Drying Time	48 hours
Viscosity @ 25c	85 - 90 ku
Solid Content By Volume	45% (± 2%)
Solid Content By Weight	38.7% (± 2%)
Specific Gravity	0.87 (± 0.03)
Dilution	Water
Average Consumption Rate	9.7 - 12.9 m ² /Ltr/Coat (depending on surface condition)
Shelf Life & Storage	2 years from the production date provided - store in sealed original packages away from direct sunlight
Specification Standards	Complying with the EG Standards 1539 /2008

Method of Use:

Surface Preparation:

- Make sure the surface is clean, clear, sound and free of grease and foreign matter.
- Prime the surface using **SUPER SEAL 123** primer from **ORIENT**.
- Level and smooth down the surface using **ACRYLIC PUTTY 1000** from **ORIENT**.
- Apply one coat of **HIGH PLAST MATT 755** emulsion from **ORIENT**.
- Apply one coat of **HIGH PLAST SILK 787** as an undercoat from **ORIENT**.

Finishing:

- Apply **SUPER GLAZE 711** by roller or brush before creating your decorative effect.
- Clean tools using white spirit.

Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are sold subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website www.orient-paints.com or call 19842.