

Product Description:

VELVET is a soft, velvet-effect coating used for interior surfaces to add luxury and warmth to interior walls. Using a combination of special-effect additives, **VELVET** transforms plain walls into vibrant three-dimensional surfaces.

Properties:

VELVET is a blend of acrylic polymers, pearlescent pigment and soft-touch additives.

Area of Use:

VELVET can be used on most interior surfaces such and is suitable for use in hotels and public buildings, as well as for domestic applications.

Advantages:

- Highly decorative.
- Easy to use.
- Non-combustible.
- Soft velvet finish.
- Environmentally friendly.

Technical Information:

Product Type	Soft Velvet-Effect Coating
Binder	Acrylic Polymer
colors	Gold - Maroon - Silver - Copper - Bronze - can be tinted using Orient Tinting System
Initial Drying Time	20 - 25 mins
Viscosity @ 25c	92 - 95 ku
Solid Content By Volume	35% (± 2%)
Solid Content By Weight	42% (± 2%)
Specific Gravity	1.13 (±0.04)
Dilution	With water if needed
Average Consumption Rate	9 – 11 m ² /Lit (depending on surface condition)
Shelf Life & Storage	2 years from the production date provided - store in sealed original packages away from direct sunlight

Method of Use:

Surface Preparation:

- Make sure the surface is clean, clear, sound and free of grease and foreign matter.
- Prime the surface using **SUPER SEAL 123** primer from **ORIENT**.
- Level and smooth down the surface using **ACRYLIC PUTTY 1000** from **ORIENT**.
- Apply one coat of **HIGH PLAST MATT 755** using the same colour as an undercoat.

Finishing:

- Apply **VELVET** using a spatula, roller or brush to achieve various attractive velvet-effect, pearlescent finishes.
- Clean tools using normal tap water.

Health & Safety:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

Notes:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **ORIENT**'s present state of knowledge and is intended to provide general information on **ORIENT**'s products and their methods of use. For more information please visit our website www.orient-paints.com or call 19842.